

AARDRUNNER UV83



FEATURES

SAFE WORKING ENVIRONMENT

- ISO ROPS/FOPS certified
- Spring applied, hydraulic release (SAHR) brakes
- Optional monitor (cameras) to increase operator's visibility during operation
- Door interlock

ENVIRONMENTAL

- Fuel efficient, clean burning Tier 2/Stage II engine
- Purifier with catalytic converter

SERVICEABILITY

- All daily check points easily reachable
- Quick and easy service to increase productivity

- Air, hydraulic and transmission filter change indicators
- Easy access to service points, filters and valve blocks

OPERATOR'S COMFORT

- Comfortable T-back seat
- Steering wheel ergonomically placed
- Single seat or dual seat compartment optional

RELIABILITY

- Proven powertrain Clark powershift transmission
- Mechanical gear control in cab
- Machine status indication lights

SPECIFICATIONS

• Vehicle height 2 202mm

■ Vehicle length 7 244mm

■ Vehicle width 1 942mm

Ground clearance 310mm

Inner turning radius 3 550mm

Outer turning radius5 500mm

■ Gross vehicle

weight empty 7 100kg

Max. carrying capacity 8 000kg

ENGINE

■ Type F6L914

Power rating 79kW at 2 300rpm

■ Torque 400Nm at 1 550rpm

■ Fuel consumption 220g/kWh

■ Engine protection As per customer

requirements

■ Air cleaner Two stage

Catalytic converter

Diluter

TRANSMISSION/TORQUE CONVERTER

 Three speed forward and reverse with integral converter

■ Dana T20 000 series

AXLES

■ Dana 112

BRAKES

Failsafe brake on all four wheels

■ Type SAHR

TYRES

■ Tyre size 35 x 15 - 15

Designed for underground mine services

Pnuematic or foam-filled

ELECTRICAL SYSTEM

24V system

Alternator 28V/55A

Isolation switch lockout

HYDRAULIC SYSTEM

System pressure 17.5MPa

Pump type Gear pump

Flow rate 2 x 36 litres/min at

2 300rpm

Hydraulic tank capacity 150 litres

Hydraulic level switch detection

FUEL SYSTEM

■ Fuel tank capacity 85 litres



SAFETY

- Fire extinguisher
- Reverse hooter
- Door interlock
- Marker lamps red/green
- Wheel stop blocks

OPTIONAL EQUIPMENT

- Manually/automatically actuated fire suppression engine shut down
- Central lubrication management system
- Automatic lubrication system
- Halogen, LED or sealed beam lights
- Electrical gear control inside cab

CRANE

Three stage telescopic boom

Max lift height 4.50m from ground

level with boom fully

extended

Max. capacity

 Reach
 Lifting

 4.05m
 735kg


 3.00m
 1 000kg

 1.90m
 1 575kg


DOCUMENTS

- Parts manual
- Technical manual
- Risk assessment


TOP VIEW



SIDE VIEW



SIDE VIEW



AARD Mining Equipment is constantly striving to improve its products and therefore reserves the right to change the designs, materials, specifications and price without prior notice.

PRODUCTS & EQUIPMENT

44 Jacobs St., Chamdor, 1739 PO Box 3992, Witbeeck 1729, South Africa

E-mail: info@aardme.co.za
Website: www.aardme.com

